CH999
A/IP(xS)-HTML Interactive Touch Screen Content Telephone

- Background music volume control
- 5 inch Interactive touch screen display
- Dial pad
- Switch data port
- Handset
- USB port
- SD port
- IR sensor
- Feature button
- Memory button
- Speakerphone
- Message light

CH999(1S)-Clock
Display phone with clock

CH999(1S)-Promo(P)
Display phone with passive Promotional display

CH999(1S)-Promo(D)
Display phone with Dynamic promotion display

Features Highlights

- 1 or 2-line
- Analog or IP(SIP)
- 1-10 one touch button
- Message waiting indicator
- Customizable faceplate
- Fixed or ascending ringing tone
- RJ45 data port
- Caller ID
- USB port
- SD Port
- IR sensor
- MP3/MP4 support
- RJ45 data port
- HTML/XML Interface
- Customizable screen content via content server

IP Features

SIP RFC 3261 compliant.
Codecs: G711a, G711u and G729
Support 802.1Q VLAN tagging
Ethernet 10/100 2-port switch
Support DHCP or static IP address

Options
WiFi

Colors
Black
Ash

CH900
Classical Series Guestroom Telephones

Standard Features

- 1-line or 2-line
- Corded or cordless
- Analog
- Surface mount technology with CPU control
- Full length customizable faceplate
- Message waiting indicator
- 1-10 programmable memory button
- Hands-free speakerphone
- With or without display
- High immunity to electro-magnetic radiation
- UV protected high quality plastic casing
- Adjustable flash-hook timer
- Handset volume control
- Speakerphone volume control
- Ringer volume control
- Auto disconnect on busy tone detection
- Redial, hold and mute
- Data port
- Incoming call indicator
- Small footprint

CH901A(xS)SP
CH901A(xD)SP
CH901AW(xS)SP
CH901AW(xD)SP

Cordless Features

- 2.4Ghz, 1.8Ghz, 1.9Ghz frequency band
- Base and handset dialing capability
- Secured digital transmission
- Handset search
- Redial capability for both base and handset
- Hold on base and handset

CH990
Contemporary Series Guestroom Telephones

Standard Features

- 1-line or 2-line
- Analog
- Surface mount technology with CPU control
- Full length customizable faceplate
- Message waiting indicator lamp with built-in
- One-touch Retrieve button
- 1-10 programmable memory button
- Hands-free speakerphone
- With or without display
- High immunity to electro-magnetic radiation
- UV protected high quality plastic casing
- Adjustable flash-hook timer
- Handset volume control
- Speakerphone volume control
- Ringer volume control
- Auto disconnect on busy tone detection
- Conference (2-line phone only)
- Redial, hold and mute
- Data port
- Incoming call indicator
- Small footprint

CH998A(xS)SP
CH998A(xD)SP
CH998A(1L)-Lobby

CH800
Lifestyle Series Guestroom Telephones

Standard Features

- 1-line or 2-line
- Analog or IP(SIP)
- Surface mount technology with CPU control
- Full length customizable faceplate
- Message waiting indicator lamp with built-in
- One-touch Retrieve button
- 1-10 programmable memory button
- Hands-free speakerphone
- With or without display
- High immunity to electro-magnetic radiation
- UV protected high quality plastic casing
- Adjustable flash-hook timer
- Handset volume control
- Speakerphone volume control
- Ringer volume control
- Auto disconnect on busy tone detection
- Conference (2-line phone only)
- Redial, hold and mute
- Data port
- Incoming call indicator
- Small footprint

IP Features

SIP RFC 3261 Compliant
Codecs: G711a, G711u, G729
Support 802.1Q VLAN tagging
Ethernet 10/100 2-port switch
Support DHCP or Static address
Power over LAN

CH800A(xS)SP
CH800A(xD)SP
CH800A(1L)-Lobby

CA700
Millennial Series Administrative office Telephones

CA720A/IP-DSP
CA720A/IP-MSP
CA720A/IP-B
CA701A (1S)
CA701A (1D)

Standard Features

- Single line
- Analog or IP(SIP)
- Mute, Flash & Redial
- Basic, Memory or display
- Ringer volume control
- 10 one-touch memory
- Message waiting light
- High immunity to EMI
- Well spaced large dial buttons
- Small footprint
- RJ45 data port
- On hook dialing or speakerphone

IP Features (For CA720 model only)

Single Line
Power over LAN
SIP compliant
One 10/100 BASE-T WAN port, used to connect broadband data network
One 10/100 BASE-T PC port, Bridged to the WAN port
Supporting DHCP Client or static IP address allocation plan
Supporting 802.1Q VLAN and VLAN Tag

CT600
Comfort Series Trimline Telephones

Standard Features

- 1-Line or 2 Line
- Analog or IP(SIP)
- Surface mount technology with CPU control
- High immunity to electro-magnetic radiation
- UV protected high quality plastic casing
- Adjustable flash-hook timer
- Auto disconnect on busy tone detection
- Redial, hold and mute
- Heat and steam resistance
- Desk or wall-mount

IP Features (For CT692 model only)

SIP RFC 3261 Compliant
Codecs: G711a, G711u, G729
Support 802.1Q VLAN tagging
Support DHCP or Static address
Power over LAN

CT692A (xS)
CT602A (xS)
CT609A (1S)