



MINIBARS THERMO-ABSORBANTS

JVD minibars are completely silent during operations. This means your guests, even the lightest sleepers, enjoy maximum comfort. JVD minibars are available in different capacities to suit your cabinet fittings, They come complete with LED interior lighting as well as quality lock. They are engineered and built to last. Purchasing a JVD silent minibar is a long-term investment in quality. Every one is built to withstand rugged, day-to-day use and to last the life of the installation.

Ventilation Requirement

When integrating the minibar into your hotel room cabinet, it is important to note that the minibar requires air ventilation inlet and outlet for best cooling performance. Below chart shows you the necessary channel for air circulation. The surrounding area of the minibar must have unhindered airflow.

To get the best performance the minibar needs at least 200cm2 free air inlet and this space should be kept until the air outlet. The rear of the minibar should be at least 20mm clear.



Utilising the most advanced thermo-absorption technology, TA minibars achieve a completely silent minibar system with absolutely no ammonia gas compound. It's complete CFC free and contains environmentally friendly, no odour, non-toxic gas which results in long lasting and quick cooling performance.



TA25 MINIBAR CAPACITY 25 L



General Specifications

- Thermo-absorption system
- Power 220~240V, 65W, 0.37kWh/24hrs
- Low energy consumption
- Automatic defrosting, quality lock included
- Interior LED, adjustable tempered glass shelf
- All round magnetic door insulation
- Reversible door
- Silent operation without vibration and noise
- CFC-free

Dimensions

- Solid door H450/W403/D352mm
- Glass door H450/W403/D343mm



REFERENCE	DESIGNATION	COLOR
TA25-BK	TA25 thermo-absorption, 25L, solid foam door	Black
TA25-GD-BK	TA25 thermo-absorption, 25L, glass door	Black